



**Pump specifications:**

Type.....	10NHTBH-F18DB
Max. flow .....	1600 m <sup>3</sup> /hour
Max. pressure .....	78 mwc
Efficiency .....	81% at BEP
Connections .....	16" x 10" ANSI
Solids handling .....	120 mm
Impeller type .....	Enclosed impeller
Casing material.....	Cast iron GG20
Casing DVS .....	Double Volute System
Pump shaft .....	Stress-proof SAE 1144
Mechanical seal .....	Cycloseal®

**FEATURES**

**Heavy Duty**

For the toughest manure and slurry applications, Cornell offers a wide range of heavy duty high head solids handling pumps. The manure pumps are all cast iron construction with hard face mechanical seals and double bearing frames.

**Energy Efficiency**

Cornell Pumps are designed to deliver Best in Class Efficiency offering the most cost effective and sustainable technology available in the market.

**Cycloseal®**

Cornell's Cycloseal design has proven itself in the toughest applications, in some cases more than tripling the normally expected mechanical seal life. With its unique deflector vanes, works with the impeller back vanes to create a cyclo-action. This action removes solids and abrasive material from the seal area.

**Cornell Pumps Europe**

A large team of professionals with over 60 years experience in the market are at your service in 7 different languages if you require any assistance with technical and commercial questions about pumps and complete pumping installations.

**Central Warehouse in The Netherlands**

- Wide range of Pumps and Parts in stock
- Dedicated customer help-desk (24/7)
- Optional European on-site servicing
- CE Machinery Directive 98/37
- ISO 9001 certified



**PERFORMANCE CURVES**  
(Density: 998.3 kg/m<sup>3</sup>)

